

DESIGNED TO:

CARRY 110% LOAD INDEFINITELY

OPEN AT 135% LOAD WITHIN 1 HOUR

FUSE	AMPERE
ADL-5	5
ADL-10	10
ADL-15	15
ADL-20	20

	_		ies.Inc. The disclosure of this work rk. The disclosure of this work net. Further dissemination or s PROHIBITED. This unpublished sral Copyright law and all rights ny Cooper Industries.Inc.	ON CONTAINED IN THIS DOCUMENT  NUDSTRIES,INC. IT IS NOT FOR ON OF THE INFORMATION DOES NOT SELL OR DISCLOSE THE INFORMATION UCTION OR USE OF THE INFORMATION OF THE RETURNED TO COOPER ETION OF THE PURPOSE FOR WHICH JEST.
		NCHES (OR U.S. 1	INDICATES CRITICAL DIMENSION OR FEATURE	SCALE 2×
	B REVISED & REDRAWN	INCHES (OR U.S. UNITS) IS THE PRIMARY UNIT OF MEASURE METRIC(mm) [INCHES]	THIRD ANGLE PROJECTION	UNLESS OTHERWISE SPECIFIED TOLERANCES TO BE:  METRIC ±.13mm INCHES ±.005"  ANGULAR ±2°
CUSTOMER PRINT	COOPER BUSSMANN St. Louis, MO 63178 C/F NO. DISTRIBUTION 5(	PAGE 1 OF 2	CK.	1-11-02 NO. ADL
RINT	800 wo 63178	SB01491	12-30-85	ADL RM FUSE

CLISTOMER DRINT

							B ADD	REV.	PAGE 2 OF 2	
							)ED "J" TO L		OF 2	
							DISTRIBUTION & REMOVEI	CHANGE	1-11-02	DATE
							ADDED "J" TO DISTRIBUTION & REMOVED "N" * REMOVED ADL-2 1/2, -3 & -30 * REDRAWN	CHANGE DESCRIPTION	INDICATING ALARM FUSE	ППГЕ
							, -3 & -30 * REDRAWN		LARM FUSE	56
							1-11-02	DATE	ADL	NO.
							SB01491	ECN #	)_	