

Search Entire Site

Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets > 954130 > 954130BF

Add to myIDT [?]

954130BF

Category: **Desktop Chipsets**

Generic Part: 954130 Market Group: PC CLOCK Description: PC MAIN CLOCK

> ICS954130 follows Intel CK410 Yellow Cover specification. This clock synthesizer combined with the ICS9FG130 provides a two-chip solution for next generation P4 Intel processors and Intel chipsets. ICS954130 is driven with a 14.318MHz

crystal. For PCI-Express platforms use the 9FG130 as the PCI-Express buffer.

Output Features:

- 2 0.7V current-mode differential CPU pairs
- 1 0.7V current-mode differential SRC pair
- 8 PCI (33MHz)
- 1 USB, 48MHz
- 1 24/48 MHz
- 1 DOT, 96MHz, 0.7V current differential pair
- 3 REF, 14.318MHz
- 1 PCI-Express seed





Parameters

Package	SSOP 48 (PV48)	
Voltage	3.3 V SSOP 48	
Package		
Speed	NA	
Temperature	С	
Status	Active	
Sample	Yes	
Minimum Order Quantity	120	
Factory Order Increment	30	

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temprature	225°C
Rebake Conditions	N/A
Length	15.9
Mark	F
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active