Status REVISION A 01/08/92 HA

REVISION B **TEMECULA** WAS CARSON 01/26/93 TS

REVISION C ADDED DCM21-PC MICROTRAN AND SAFETY 01/20/96 TS

REVISION D ADDED RoHS. UL1459 WAS UL1863. DIM 20.3(0.799) WAS 19.8(0.781) 10/17/06 MP

TELECOMMUNICATION DRY COUPLING TRANSFORMER DESIGNED TO OPERATE AT A MAX LEVEL OF +7dBm AND TO REFLECT A PRIMARY SOURCE IMPEDANCE OF APPROXIMATELY 600ΩCT WITH 600ΩCT LOAD ON SECONDARY

- A. Electrical Specifications (@ 25°C)
  - 1. Pri Source Impedance;  $600\Omega$  CT
  - 2. Sec Load Impedance;  $600\Omega$  CT
  - 3. Operating Level; -45 dBm to +7 dBm
  - 4. Insertion Loss;
    - 1.4 dB MAX @ 1 KHz, 0 dBm
  - 5. Frequency Response;

 $\pm 0.5$  dB 300 Hz to 3.5 KHz @ 0 dBm

6. Primary Impedance;

 $600 \Omega + 15\%$ , -5% @ 300 Hz to 3.5 KHz, OdBm 600  $\Omega$  +10%, -5% @ 500 Hz to 2.5 KHz, 0dBm

7. Longitudinal Balance;

60 dB MIN @ 200 Hz to 1 KHz 40 dBm MIN @ 4 KHz

8. DC Resistance:

44 Ω ±20% 56 Ω ±20% (1-3) =(4-6) =

9. Turns Ratio; (1-3): (4-6) = 1 : 1.00 ±2%

10. Dielectric Strength;

1500 Vrms 1 minute @ Pri to Sec, and Pri to Core

1000 Vrms 1 minute @ Sec to Core

11. Total Harmonic Distortion;

0.5% MAX @ 300 Hz to 3.5 KHz, 0 dBm

12. Induced Voltage; (1-3) 250 Vrms 5 KHz 1 minute

B. Marking; TTC-108, TAMURA, DCM21-PC, MICROTRAN, safety agency logos, 196-date code and country of origin


C. Safety; CSA-22.2 No. 66-M1988 File No. LR81383

UL 1459 File No. E142035

D. Schematic Diagram <u>PRI</u> 3<sub>0-</sub> 600ΩCT  $600\Omega\,\text{CT}$ 

MICROTRAN and DCM21-PC -

Red Dot PIN 1




UL# E142035

Safety logos -

E. Mechanical Specifications

19.1(0.75) MAX

Date Code and Country of Origin



3.81(0.150) MIN <sup>→</sup>

DWG CONTROL NO.

P-A1-10017

ACAD\TTC\A1100171.DWG

CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

- 0.40 ±0.1(0.016 ±0.004)

3

2

 $1.02 \pm 0.25(0.04 \pm 0.01) -$ 

REV

 $10.7 \pm 0.5(0.421 \pm 0.020)$ <sub>5</sub>4.75 ±0.25(0.187 ±0.010)

 $4.75 \pm 0.25(0.187 \pm 0.010)$ 

TELECOMMUNICATION COUPLING **TRANSFORMER** 

TAMURA CORPORATION OF AMERICA

43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624 (951) 699-1270 FAX 9516769482

17.5(0.689) MAX  $\rightarrow$ 

+20.3(0.799) MAX

TTC-108

MODEL SPECIFICATION

DIM: mm[In] SCL: 1/1

SH: 1 0F

K. BRENNAN **ENGINEER:** 

TOLERANCES (mm)

 $4 \le 20 \pm 0.3$ 

 $20 \le 50 \pm 0.4$ 

PREPARED BY:

 $4 \pm 0.2$ 

M. PITCHAI

QUALITY CONTROL:

T. CLEM APPROVED:

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING. Y. SEKIGUCHI