Change Notice

G Indicators

Changes to LED Specifications for G Series Indicators

Type of Change:

✓ Engineering✓ Part Number✓ Product✓ Appearance

The LEDs for G Series Indicators will be changing. This will result in different electrical values for Red and Green LEDs. Although Yellow LEDs will also be replaced, there is no difference in the specifications. The revisions apply to standard and custom indicators. Following are comparisons between the specifications and a table of effected standard part numbers.






CHANGES TO LED SPECIFICATIONS										
Electrical specifications are determinat a basic temperature of 25°C.	Before Change			After Change						
		С	E	F	C	E	F			
LED is colored in OFF state	Color	Red	Yellow	Green	Red	Yellow	Green			
Maximum Forward Current	I _{FM}	30mA	30mA	25mA	30mA	30mA	30mA			
Typical Forward Current	I _F	20mA	20mA	20mA	20mA	20mA	20mA			
Forward Voltage	V _F	2.0V	2.1V	2.25V	2.1V	2.1V	2.2V			
		I _F = 20mA								
Maximum Reverse Voltage	V _{RM}	5V	5V	5V	5V	5V	5V			
Current Reduction Rate Above 25°C	ΔI_{F}	0.40mA/°C	0.40mA/°C	0.33mA/°C	0.40mA/°C	0.40mA/°C	0.40mA/°C			
Ambient Temperature Range	·	−25°C ~ +85°C)					

Notes

- The LED circuit is isolated and requires an external power source.
- If the source voltage is greater than the LED's rated voltage, a ballast resistor must be connected in series with the LED. The resistor value can be calculated by using the formula shown here.
- There are no changes to any other specifications or external dimensions.
- · Contact the factory if further details are needed.



G Indicator Part Numbers										
G01PC	G01PE	G01PF	G01VC	G01VE	G01VF					

Effective Date

LED changes for G Series Indicators will be effective April 2019.



www.nkkswitches.com • 1.877.2BUYNKK (228.9655)

7850 East Gelding Drive • Scottsdale, AZ 85260 • Telephone 480.991.0942 • Fax 480.998.1435