



BAS19W-BAS21W SURFACE MOUNT FAST SWITCHING DIODE



Features

- High Conductance
- Fast Switching
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose and Switching
- Plastic Material - UL Recognition Flammability Classification 94V-0
- This is a Pb - Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Schematic & Pin Configuration



Mechanical Characteristics

- Case: SOT-323, Molded Plastic
- Terminals: Plated leads Solderable per MIL-STD-202, Method 208
- Weight: 0.006g
- Mounting Position: Any

Maximum Ratings@T_A=25°C unless otherwise specified

Characteristic	Symbol	BAS19W	BAS20W	BAS21W	Units
Non-Repetitive Peak Reverse Voltage	V _{RM}	120	200	250	V
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V _{RRM} V _{RWM} V _R	100	150	200	V
RMS Reverse Voltage(Note 1)	V _{R(RMS)}	70	105	140	V
Forward Continuous Current (Note 1)	I _{FM}	400			mA
Average Rectified Output Current(Note 1)	I _o	200			mA
Non-Repetitive Peak Forward Surge Current @t=1us	I _{FSM}	2.5			A
Power Dissipation	P _D	200			mW
Thermal Resistance, Junction to Ambient(Note 1)	R _{θJA}	625			°C/W
Junction and Storage Temperature Range	T _J , T _{STG}	-65 to +150			°C

Electrical Characteristics @ $T_A=25^{\circ}\text{C}$ unless otherwise specified

Characteristic	Symbol	Min	Max	Units	Test Condition
Forward Voltage*	V_F	-	1.00 1.25	V	@ $I_F=100\text{mA}$ @ $I_F=200\text{mA}$
Reverse Leakage Current*	I_R	-	100	nA	@Rated DC Blocking Voltage
Capacitance between terminals	C_T	-	5	pF	$V_R=0\text{V}$, $f=1.0\text{MHz}$
Reverse Recovery Time	t_{rr}	-	50	ns	$I_F=I_R=30\text{mA}$, $I_{RR}=0.1 \times I_R$, $R_L=100\Omega$

* Pulse width < 300 μs , duty cycle < 2%
Note: 1. Device mounted on fiberglass substrate 40x40x1.5mm

Ratings and Characteristics Curves




Fig. 1 Forward Characteristics




Fig. 2 Leakage Current vs Junction Temperature

Ordering Information

Device	Package	Shipping
BAS19W-BAS21W	SOT-323 (Pb-Free)	3000pcs / reel

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

Marking Diagram


Marking before 16441(Date Code)

Part Number	Device Marking Code
BAS19W	A8
BAS20W	A80
BAS21W	A82

Marking from 16441(Date Code)


Part Number	Device Marking Code
BAS19W	KA8
BAS20W	KT2
BAS21W	KT3

Mechanical Dimensions SOT-323



SYMBOL	Millimeters		Inches	
	MIN.	MAX.	MIN.	MAX.
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP.		0.026 TYP.	
e1	1.200	1.400	0.047	0.055
L	0.525 REF.		0.021 REF.	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

Carrier Tape Specification SOT-323



SYMBOL	Millimeters	
	Min.	Max.
A	2.20	2.30
B	2.50	2.60
C	1.14	1.24
d	1.45	1.65
E	1.65	1.85
F	3.40	3.60
P	3.90	4.10
P0	3.90	4.10
P1	1.90	2.10
W	7.90	8.30



DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..