| . 6 | English 简体 | ☞中文│日本語 | Search Entire Site GO Contact IDT Investors Press |
|---|---|--|--|
| | About IDT Products | Applications | Support myIDT |
| ackage Search Parametric Search Cross Reference Search Green | & Rohs Calculators Thermal Data | Reliability & Quality Mi | liitary |
| Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by KLFT | Chipset Vendor > Desktop Chipsets > | Add to myIDT [?] | You may also like |
| т | | | |
| Desktop Chipsets | | | Time is |
| 954305 | | | |
| PC CLOCK | | | money |
| mobile systems built with Intel P4-M processors and Intel mol | bile chipsets. The ICS954305 is dri | | |
| Output Features: | | | |
| • 2 - 0.7V current-mode differential CPU pairs | | | |
| · · · · · · · · · · · · · · · · · · · | • | | |
| • 4 - PCI (33MHz) | | | |
| | | | |
| 1 - OSB, 40MHZ 1 - DOT, 96MHz, 0.7V current differential pair | | | |
| • 2 - REF, double-strength 14.318MHz | | | |
| 1 - 0.7V current-mode differential LCD spread/SRC selecta 1 - 100MHz/96MHz selectable LCD spread clock | ble clock | | |
| | Ackage Search Parametric Search Cross Reference Search Green Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by KLFT T Desktop Chipsets 954305 PC CLOCK PC MAIN CLOCK The ICS954305 is a CK410M+ Yellow Cover clock synthesizer mobile systems built with Intel P4-M processors and Intel mo 14.318MHz crystal and generates CPU outputs up to 400MHz. Output Features: 9 - 0.7V current-mode differential CPU pairs 9 - 0.7V current-mode differential SRC pair for SATA and PC 1 - 0.7V current-mode differential CPU/SRC selectable pair 4 - PCI (33MHz) 1 - PCICLK_F, (33MHz) free-running 1 - USB, 48MHz 1 - DOT, 96MHz, 0.7V current differential pair 2 - REF, double-strength 14.318MHz 1 - 0.7V current-mode differential LCD spread/SRC selectable | About IDT Products ackage Search Parametric Search Cross Reference Search Green & RoHS Calculators Thermal Data Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets > KLFT FT Desktop Chipsets 954305 PC CLOCK PC MAIN CLOCK The ICS954305 is a CK410M+ Yellow Cover clock synthesizer. The ICS954305 provides a single mobile systems built with Intel P4-M processors and Intel mobile chipsets. The ICS954305 is dri 14.318MHz crystal and generates CPU outputs up to 400MHz. Output Features: • 2 - 0.7V current-mode differential CPU pairs • 9 - 0.7V current-mode differential CPU/SRC selectable pair • 4 - PCI (33MHz) • 1 - DCICLK_F, (33MHz) free-running • 1 - DCT, 96MHz, 0.7V current differential pair • 2 - REF, double-strength 14.318MHz • 1 - 0.7V current-mode differential pair • 2 - REF, double-strength 14.318MHz | About IDT Products Applications ackage Search Parametric Search Cross Reference Search Green & RoHS Calculators Thermal Data Reliability & Quality M Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets > Add to myIDT [?] ET Desktop Chipsets 954305 PC CLOCK PC MAIN CLOCK The ICS954305 is a CK410M+ Yellow Cover clock synthesizer. The ICS954305 provides a single-chip solution for mobile systems built with Intel P4-M processors and Intel mobile chipsets. The ICS954305 is driven with a 14.318MHz crystal and generates CPU outputs up to 400MHz. Output Features: 2 - 0.7V current-mode differential CPU pairs 9 - 0.7V current-mode differential CPU pairs 9 - 0.7V current-mode differential CPU/SRC selectable pair 4 - PCI (33MHz) 1 - DCICLK_F, (33MHz) free-running 1 - USB, 48MHz 1 - DOT, 96MHz, 0.7V current differential pair 2 - REF, double-strength 14.318MHz 1 - 0.7V current-mode differential pair 2 - REF, double-strength 14.318MHz 1 - 0.7V current-mode differential pair 2 - REF, double-strength 14.318MHz 1 - 0.7V current-mode differential pair |

Parameters

| Package | VFQFPN 72 (NPG72) |
|-------------------------|-------------------|
| Voltage | 3.3 V |
| Package | V FQFPN 72 |
| Speed | NA |
| Temperature | С |
| Status | Active |
| Sample | No |
| Minimum Order Quantity | 500 |
| Factory Order Increment | 500 |
| | |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Туре | Title | Size | Revision Date |
|--------------------------|---|-----------|------------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 |
| Product Change Notice | PCN# : A0701-02 Punch Singulation as Alternate Assembly Process for 10mm x 10mm VFQFP-N-72 | 514 KB | 01/30/2007 |
| | PCN# : A0701-02R1 Punch Singulation as Alternate Assembly Process for 10mm x 10mm VFQFP-N-72 and transfer Test facility from IDT Singapore to IDT Penang | 453 KB | 04/24/2007 |

Package

| Description | VFQFP-N 10.0 X 10.0 X 0.9MM- NO LEA |
|-------------|-------------------------------------|
| Class | PLASTIC |
| Length | 10.0 |
| Mark | NLG |
| Width | 10.0 |
| Pitch | 0.5 |
| Thickness | 1.0 |
| Status | Active |

Home | Site Map | Legal | Careers | Contact Us | Quality | **ISS** What is this? Use of this website signifies your agreement to the acceptable use and privacy policy. Copyright © 1997-2008 Integrated Device Technology, Inc. All Rights Reserved.