### Product data sheet Characteristics

## **XBTZGJBOX**

# junction box for advanced hand-held terminal





#### Main

| Magelis XBTGH                      |              |
|------------------------------------|--------------|
| Junction box                       |              |
| For XBTGH advanced hand-held panel |              |
|                                    | Junction box |

#### Complementary

| [Us] rated supply voltage | 24 V DC  |
|---------------------------|--|
| Supply voltage limits     | 19.228.8 V   |
| Inrush current            | 30 A   |
| Power consumption in W    | 6.3 W  |
| Electrical connection     | 1 connector 24-pin connector hand-held panel 1 connector RJ45 Ethernet TCP/IP 1 male connector SUB-D 9 RS232C/RS422/RS485 <= 115.2 kbits/s COM1 serial link Screw terminal block 24 inputs/outputs |
| Port Ethernet             | 10BASE-T/100BASE-TX  |
| Enclosure Material        | PPT  |
| Fixing mode               | By 4 M4 screws 1.5 to 10 mm thick panel<br>Clip-on 35 mm symmetrical DIN rail  |
| Marking                   | CE   |

#### Environment

| Immunity to microbreaks Standards     | 10 ms  |  |
|---------------------------------------|--|--|
| Ctandarda                             |  |  |
| Standards                             | FCC Class A                                  |  |
|                                       | EN 61131-2                                   |  |
|                                       | IEC 61000-6-2                                |  |
|                                       | UL 508                                       |  |
| Product Certifications                | CULus  |  |
|                                       | C-tick                                       |  |
| Ambient Air Temperature for Operation | 32122 °F (050 °C)                            |  |
| Ambient Air Temperature for Storage   | -4140 °F (-2060 °C)                          |  |
| Operating altitude                    | <= 6561.68 ft (2000 m)                       |  |
| IP degree of protection               | IP20 rear panel)                             |  |
|                                       | IP65 front panel)                            |  |
| Shock resistance                      | 15 gn 11 ms IEC 60068-2-27                   |  |
| Vibration resistance                  | 1 gn 9150 Hz)                                |  |
|                                       | 3.5 mm 59 Hz)                                |  |
| Relative Humidity                     | 090 % without condensation or dripping water |  |
| Resistance to electrostatic discharge | 6 kV IEC 61000-4-2 level 3                   |  |
| Resistance to electromagnetic fields  | 9.14 V/m (10 V/m) IEC 61000-4-3              |  |
| Resistance to fast transients         | 2 kV IEC 61000-4-4 level 3                   |  |

### Ordering and shipping details

| Category              | 22569-MAGELIS XBT-GT (AND XBT-G) |
|-----------------------|----------------------------------|
| Discount Schedule     | MC2                              |
| GTIN                  | 3595864003191                    |
| Nbr. of units in pkg. | 1                                |
| Package weight(Lbs)   | 2.58 lb(US) (1.172 kg)           |
| Returnability         | Yes                              |
| Country of origin     | JP                               |

### Packing Units

| <b>3</b>                     |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 6.42 in (16.3 cm)       |
| Package 1 width              | 8.50 in (21.6 cm)       |
| Package 1 Length             | 10.83 in (27.5 cm)      |
| Unit Type of Package 2       | S04                     |
| Number of Units in Package 2 | 2                       |
| Package 2 Weight             | 6.80 lb(US) (3.084 kg)  |
| Package 2 Height             | 11.81 in (30.0 cm)      |
| Package 2 width              | 15.75 in (40.0 cm)      |
| Package 2 Length             | 23.62 in (60.0 cm)      |
| Unit Type of Package 3       | P12                     |
| Number of Units in Package 3 | 30                      |
| Package 3 Weight             | 110.23 lb(US) (50.0 kg) |
| Package 3 Height             | 35.43 in (90.0 cm)      |
| Package 3 width              | 31.50 in (80.0 cm)      |
| Package 3 Length             | 47.24 in (120.0 cm)     |

#### Offer Sustainability

| Sustainable offer status   | Green Premium product   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation           | ☑ REACh Declaration   |
| REACh free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS  Declaration   |
| Mercury free               | Yes   |
| RoHS exemption information | €Yes  |
| China RoHS Regulation      | China RoHS Declaration  |
| Environmental Disclosure   | Product Environmental Profile   |
| Circularity Profile        | End Of Life Information   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

### Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|