



ELECTRONICS, INC.  
44 FARRAND STREET  
BLOOMFIELD, NJ 07003  
(973) 748-5089  
<http://www.nteinc.com>



## NTE53006 thru NTE53010 Silicon Bridge Rectifier, 15A

### **Features:**

- Low Forward Voltage Drop
- High Current Capability
- High Reliability
- High Surge Current Capability
- Ideal for PC Boards
- Mounting Position: Any

**Maximum Ratings and Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified.  
Single Phase, Half Wave, 60Hz, Resistive or Inductive Load, Note 1.)

Maximum Recurrent Peak Reverse Voltage,  $V_{RRM}$

NTE53006 .....	200V
NTE53008 .....	600V
NTE53010 .....	1000V

Working Peak Reverse Voltage,  $V_{RWM}$

NTE53006 .....	200V
NTE53008 .....	600V
NTE53010 .....	1000V

Maximum RMS Bridge Input Voltage,  $V_{RMS}$

NTE53006 .....	140V
NTE53008 .....	420V
NTE53010 .....	700V

Maximum DC Blocking Voltage,  $V_{DC}$

NTE53006 .....	200V
NTE53008 .....	600V
NTE53010 .....	1000V

Maximum Average Forward Rectified Output Current ( $T_C = +100^\circ\text{C}$ , Note 2),  $I_{O(AV)}$  ..... 15A

Peak Forward Surge Current (8.3ms single half wave superimposed on rated load),  $I_{FSM}$  ..... 240A

Maximum Forward Voltage Drop (Per element at 7.5A),  $V_F$  ..... 1.05V

Maximum Reverse Current at Rated DC Blocking Voltage Per Element,  $I_R$

$T_A = +25^\circ\text{C}$ .....	10 $\mu\text{A}$
$T_A = +125^\circ\text{C}$ .....	250 $\mu\text{A}$

Typical Thermal Resistorance (Per element)

Junction-to-Ambient (Note 3), $R_{thJA}$ .....	22 $^\circ\text{C}/\text{W}$
Junction-to-Case (Note 2), $R_{thJC}$ .....	1.5 $^\circ\text{C}/\text{W}$

Operating Temperature Range,  $T_J$  .....  $-55^\circ$  to  $+150^\circ\text{C}$

Storage Temperature Range,  $T_{stg}$  .....  $-55^\circ$  to  $+150^\circ\text{C}$

Note 1. For capacitive load, derate current by 20%.

Note 2. Device mounted on a 300mm x 300mm x 1.6mm thick Cu plate heatsink.

Note 3. Device mounted on a PC board without heatsink.

