Material	High Conductivity Seamless Copper Tube						
Plating	Electro-Tin						
Wire Size	1 AWG	1	\$				Wire inspection
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	.75±.04	PANDUIT	1 STR CU LCC1-12WF			window
Wire Strip Length	1-7/16 in.						
Stud Size	1/2 in.	-	.63±.04 -	— 1.75±.02 –	-	53±.02 DIA (2) PLS	
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.		09±.01			(2) + 23	
UL Temperature Rating	90° C		4	— 3.00±.04 –	-		
C.S.A Certified Wire Connector	Yes						
Panduit Color Code on Barrel	GREEN						, i
Panduit Die Index No. on Barrel	P37				90°±5°		 1.88 REF
Alternate Industry Die Index No. () on Barrel	(11)					1.36±.0	4
					.36±.01 —		C
CERTIFIE	D LISTED Wire Connector		-	3.68	.47±.01 —	B€	eveled wire entry

						PANDU	CORP.	TINLEY PARK, ILLINOIS
						Copportug Two Hole	LCC1-12WF-E	
01	11/03	DRL	DRL	TONGUE WIDTH WAS .79	11257	Copper Lug - Two-note	e, cong banei wiin	Window, 90° Angle Tongue
REV	DATE	BY	СНК	DESCRIPTION	ECN	SCALE N/A	DRAWING NO / CAD FIL	LCC1-12WF-CUST

PANDUIT

Color coded
 barrel markings